



Produktinformation		Product information	
Produktbeskrivning: Mitträcke med två W-profil monterat på C120 ständare monterade i mark		Product description: Safety barrier with two A-profiles fixed at C120 post installed in soil	
Harmoniserad standard: EN1317-5:2007/A2:2012		Harmonised standard: EN1317-5:2007/A2:2012	
Ständaravstånd (m)	2	Post spacing (m)	2
Kapacitetsklass	H1	Containment level	H1
Normaliserad arbetsbredd (klass)	W3	Normalised working width (class)	W3
Normaliserad arbetsbredd (m)	1.0	Normalised working width (m)	1.0
Normaliserad dynamisk utböj. (m)	0.8	Normalised dynamic defl. (m)	0.8
Norm. fordonsinträngning (klass)	VI8	Norm. vehicle intrusion (class)	VI8
Norm. fordonsinträngning (m)	2.6	Norm. vehicle intrusion (m)	2.6
Skaderiskklass	A	Impact severity level	A
Konstruktionsbredd (m)	0.28	Construction width (m)	0.28
Konstruktionshöjd (m)	0.77	Construction height (m)	0.77
Motstånd mot snöplogning(klass)	3	Resistance to snow removal(class)	3
Beständighet: Varmförzinkad enligt SS-EN ISO 1461:2009 Nationell Bilaga Fe/Zn 115		Durability: Hot dip galvanized coatings according to SS-EN ISO 1461:2009 National Annex. Fe/Zn 115	