



Produktinformation			Product information		
<b>Produktbeskrivning:</b> Vägräcke med K-profil monterat på sigma ståndare monterade i mark			<b>Product description:</b> Safety barrier with K-profile fixed at sigma post installed in soil		
<b>Harmoniserad standard:</b> EN1317-5:2007/A2:2012			<b>Harmonised standard:</b> EN1317-5:2007 / A2:2012		
<b>Kapacitetsklass</b>	N2		<b>Containment level</b>	N2	
<b>Ståndaravstånd (m)</b>	2	4	<b>Post spacing (m)</b>	2	4
<b>Normaliserad arbetsbredd (klass)</b>	W5	W6	<b>Normalised working width (class)</b>	W5	W6
<b>Normaliserad arbetsbredd (m)</b>	1.7	2.0	<b>Normalised working width (m)</b>	1.7	2.0
<b>Normaliserad dynamisk utbøj. (m)</b>	1.5	1.9	<b>Normalised dynamic defl. (m)</b>	1.5	1.9
<b>Skaderiskklass</b>	A		<b>Impact severity level</b>	A	
<b>Konstruktionsbredd (m)</b>	0.14		<b>Construction width (m)</b>	0.14	
<b>Konstruktionshöjd (m)</b>	0.62		<b>Construction height (m)</b>	0.62	
<b>Motstånd mot snöplogning(klass)</b>	4		<b>Resistance to snow removal(class)</b>	4	
<b>Beständighet:</b> Varmförzinkad enligt SS-EN ISO 1461:2009 Nationell Bilaga Fe/Zn 115			<b>Durability:</b> Hot dip galvanized coatings according to SS-EN ISO 1461:2009 National Annex. Fe/Zn 115		