



Produktinformation	Product information
Produktbeskrivning: Räcke med SF-profil som navföljare, 120x80 som toppföljare monterat på □ 55 ståndare.	Product description: Safety barrier with SF-profile as safety rail, 120x80 as top rail fixed at □ 55 post.
Harmoniserad standard: EN1317-5:2007/A2:2012	<i>Harmonised standard:</i> EN1317-5:2007 / A2:2012
Kapacitetsklass H2	Containment level H2
Ståndaravstånd (m) 2.0	Post spacing (m) 2.0
Norm. fordonsinträngning (klass) VI3	Norm. vehicle intrusion (class) VI3
Norm. fordonsinträngning (m) 0.9	Norm. vehicle intrusion (m) 0.9
Norm. arbetsbredd (klass) W2	Norm. working width (class) W2
Norm. arbetsbredd (m) 0.8	Norm. working width (m) 0.8
Norm. dynamisk utböjning (m) 0.5	Norm. dynamic deflection (m) 0.5
Skaderiskklass B	Impact severity level B
Konstruktionsbredd (m) 0.20	Construction width (m) 0.20
Konstruktionshöjd (m) 1.2	Construction height (m) 1.2
Motstånd mot snöplogning (klass) 4	Resistance to snow removal(class) 4
Beständighet: Varmförzinkad enligt SS-EN ISO 1461:2009 Nationell Bilaga Fe/Zn 115	Durability: Hot dip galvanized coatings according to SS-EN ISO 1461:2009 National Annex. Fe/Zn 115