



<b>Produktinformation</b>	<b>Product information</b>
<b>Produktbeskrivning:</b> Vägräcke med SF-profil monterat på C120 ståndare monterade i mark	<b>Product description:</b> Safety barrier with SF-profile fixed at C120 post installed in soil
<b>Harmoniserad standard:</b> EN1317-5:2007/A2:2012	<b>Harmonised standard:</b> EN1317-5:2007 / A2:2012
<b>Kapacitetsklass</b> N2	<b>Containment level</b> N2
<b>Ständaravstånd (m)</b> 4.0	<b>Post spacing (m)</b> 4.0
<b>Norm. arbetsbredd (klass)</b> W3	<b>Norm. working width (class)</b> W3
<b>Norm. arbetsbredd (m)</b> 1.0	<b>Norm. working width (m)</b> 1.0
<b>Norm. dynamisk utböjning (m)</b> 1.0	<b>Norm. dynamic deflection (m)</b> 1.0
<b>Skaderiskklass</b> A	<b>Impact severity level</b> A
<b>Konstruktionsbredd (m)</b> 0.18	<b>Construction width (m)</b> 0.18
<b>Konstruktionshöjd (m)</b> 0.69	<b>Construction height (m)</b> 0.69
<b>Motstånd mot snöplogning(klass)</b> 4	<b>Resistance to snow removal(class)</b> 4
<b>Beständighet:</b> Varmförzinkad enligt SS-EN ISO 1461:2009 Nationell Bilaga Fe/Zn 115	<b>Durability:</b> Hot dip galvanized coatings according to SS-EN ISO 1461:2009 National Annex. Fe/Zn 115