



Produktinformation		Product information	
Produktbeskrivning: Vagräcke med W-profil monterat på sigma ständare monterade i mark		Product description: Safety barrier with A-profile fixed at sigma post installed in soil	
Harmoniserad standard: EN1317-5:2007/A2:2012		Harmonised standard: EN1317-5:2007 / A2:2012	
Kapacitetsklass	N2	Containment level	N2
Ständaravstånd (m)	2 4	Post spacing (m)	2 4
Normaliserad arbetsbredd (klass)	W4 W5	Normalised working width (class)	W4 W5
Normaliserad arbetsbredd (m)	1.1 1.7	Normalised working width (m)	1.1 1.7
Normaliserad dynamisk utböj. (m)	0.9 1.5	Normalised dynamic defl. (m)	0.9 1.5
Skaderiskklass	A	Impact severity level	A
Konstruktionsbredd (m)	0.18	Construction width (m)	0.18
Konstruktionshöjd (m)	0.70	Construction height (m)	0.70
Motstånd mot snöplogning(klass)	3	Resistance to snow removal(class)	3
Beständighet: Varmförzinkad enligt SS-EN ISO 1461:2009 Nationell Bilaga Fe/Zn 115		Durability: Hot dip galvanized coatings according to SS-EN ISO 1461:2009 National Annex. Fe/Zn 115	