



Produktinformation		Product information	
Produktbeskrivning: Väggräcke med två rör monterat på C120 ständare monterade i mark		Product description: Safety barrier with two pipes fixed at C120 post installed in soil	
Harmoniserad standard: EN1317-5:2007/A2:2012		Harmonised standard: EN1317-5:2007 / A2:2012	
Kapacitetsklass	N2	Containment level	N2
Ständaravstånd (m)	4.0	Post spacing (m)	4.0
Norm. arbetsbredd (klass)	W3	Norm. working width (class)	W3
Norm. arbetsbredd (m)	0.9	Norm. working width (m)	0.9
Norm. dynamisk utböjning (m)	0.8	Norm. dynamic deflection (m)	0.8
Skaderiskklass	A	Impact severity level	A
Konstruktionsbredd (m)	0.21	Construction width (m)	0.21
Konstruktionshöjd (m)	0.73	Construction height (m)	0.73
Motstånd mot snöplogning(klass)	4	Resistance to snow removal(class)	4
Beständighet: Varmförzinkad enligt SS-EN ISO 1461:2009 Nationell Bilaga Fe/Zn 115		Durability: Hot dip galvanized coatings according to SS-EN ISO 1461:2009 National Annex. Fe/Zn 115	