



Produktinformation		Product information	
<b>Produktbeskrivning:</b> Räcke med W profil som navföljare, 120x80 som toppföljare monterat på 60x60x8 ståndare.		<b>Product description:</b> Safety barrier with W profile as safety rail, 120x80 as top rail fixed at 60x60x8 post.	
<b>Harmoniserad standard:</b> EN1317-5:2007/A2:2012		<b>Harmonised standard:</b> EN1317-5:2007 / A2:2012	
<b>Kapacitetsklass</b>	H2	<b>Containment level</b>	H2
<b>Ständaravstånd (m)</b>	2.0	<b>Post spacing (m)</b>	2.0
<b>Norm. fordonsinträngning (klass)</b>	VI4	<b>Norm. vehicle intrusion (class)</b>	VI4
<b>Norm. fordonsinträngning (m)</b>	1.1	<b>Norm. vehicle intrusion (m)</b>	1.1
<b>Norm. arbetsbredd (klass)</b>	W2	<b>Norm. working width (class)</b>	W2
<b>Norm. arbetsbredd (m)</b>	0.7	<b>Norm. working width (m)</b>	0.7
<b>Norm. dynamisk utböjning (m)</b>	0.5	<b>Norm. dynamic deflection (m)</b>	0.5
<b>Skaderiskklass</b>	B	<b>Impact severity level</b>	B
<b>Konstruktionsbredd (m)</b>	0.21	<b>Construction width (m)</b>	0.21
<b>Konstruktionshöjd (m)</b>	1.2	<b>Construction height (m)</b>	1.2
<b>Motstånd mot snöplogning (klass)</b>	3	<b>Resistance to snow removal(class)</b>	3
<b>Beständighet:</b> Varmförzinkad enligt SS-EN ISO 1461:2009 Nationell Bilaga Fe/Zn 115		<b>Durability:</b> Hot dip galvanized coatings according to SS-EN ISO 1461:2009 National Annex. Fe/Zn 115	