



| Produktinformation | | Product information | |
|--|------|---|------|
| Produktbeskrivning: Väggräcke med M profil monterat på C110 ståndare monterade i mark | | Product description: Safety barrier with M profile fixed at C110 post installed in soil | |
| Harmoniserad standard: EN1317-5:2007/A2:2012 | | Harmonised standard: EN1317-5:2007 / A2:2012 | |
| Kapacitetsklass | N2 | Containment level | N2 |
| Ståndaravstånd (m) | 4.0 | Post spacing (m) | 4.0 |
| Norm. arbetsbredd (klass) | W4 | Norm. working width (class) | W4 |
| Norm. arbetsbredd (m) | 1.3 | Norm. working width (m) | 1.3 |
| Norm. dynamisk utböjning (m) | 1.1 | Norm. dynamic deflection (m) | 1.1 |
| Skaderiskklass | A | Impact severity level | A |
| Konstruktionsbredd (m) | 0.20 | Construction width (m) | 0.20 |
| Konstruktionshöjd (m) | 0.60 | Construction height (m) | 0.60 |
| Motstånd mot snöplogning(klass) | 4 | Resistance to snow removal(class) | 4 |
| Beständighet: Varmförzinkad enligt SS-EN ISO 1461:2009 Nationell Bilaga Fe/Zn 115 | | Durability: Hot dip galvanized coatings according to SS-EN ISO 1461:2009 National Annex. Fe/Zn 115 | |