



Produktinformation			Product information		
Produktbeskrivning: Vägräcke med W-profil monterat på StalPro Sigma ständare monterade i mark			Product description: Safety barrier with A-profile fixed at StalPro Sigma post installed in soil		
Harmoniserad standard: EN1317-5:2007/A2:2012			Harmonised standard: EN1317-5:2007/A2:2012		
Ständaravstånd (m)	4		Post spacing (m)	4	
Kapacitetsklass	N2	H1	Containment level	N2	H1
Norm. arbetsbredd (klass)	W3	W3	Norm. working width (class)	W3	W3
Norm. arbetsbredd (m)	1.0	1.0	Norm. working width (m)	1.0	1.0
Norm. fordonsinträngning (klass)	-	VI5	Norm. vehicle intrusion (class)	-	VI5
Norm. fordonsinträngning (m)	-	1.7	Norm. vehicle intrusion (m)	-	1.7
Norm. dynamisk utböj. (m)	0.9	0.9	Norm. dynamic defl. (m)	0.9	0.9
Skaderiskklass	A		Impact severity level	A	
Konstruktionsbredd (m)	0.22		Construction width (m)	0.22	
Konstruktionshöjd (m)	0.75		Construction height (m)	0.75	
Motstånd mot snöplogning(klass)	3		Resistance to snow removal(class)	3	
Beständighet: Varmförzinkad enligt SS-EN ISO 1461:2009 Nationell Bilaga Fe/Zn 115			Durability: Hot dip galvanized coatings according to SS-EN ISO 1461:2009 National Annex. Fe/Zn 115		