



Produktinformation		Product information	
Produktbeskrivning: Väggräcke med W-profil monterat på C100 ständare monterade i mark		Product description: Safety barrier with A-profile fixed at C100 post installed in soil	
Harmoniserad standard: EN1317-5:2007/A2:2012		Harmonised standard: EN1317-5:2007/A2:2012	
Ständaravstånd (m)	1.33	Post spacing (m)	1.33
Kapacitetsklass	H2	Containment level	H2
Normaliserad arbetsbredd (klass)	W3	Normalised working width (class)	W3
Normaliserad arbetsbredd (m)	1.0	Normalised working width (m)	1.0
Normal. fordonsinträngning (kl.)	VI6	Normal. vehicle intrusion (cl.)	VI6
Normal. fordonsinträngning (m)	1.8	Normal. vehicle intrusion (m)	1.8
Normaliserad dynamisk utböj. (m)	0.7	Normalised dynamic defl. (m)	0.7
Skaderiskklass	A	Impact severity level	A
Konstruktionsbredd (m)	0.18	Construction width (m)	0.18
Konstruktionshöjd (m)	0.75	Construction height (m)	0.75
Motstånd mot snöplogning (klass)	3	Resistance to snow removal(class)	3
Beständighet: Varmförzinkad enligt SS-EN ISO 1461:2009 Nationell Bilaga Fe/Zn 115		Durability: Hot dip galvanized coatings according to SS-EN ISO 1461:2009 National Annex. Fe/Zn 115	